

## Split klima uređaj

Outdoor unit	Single inverter	RAS-10PAVPG-E
Indoor unit	DAISEIKAI 9	RAS-10PKVPG-E

Function		Design load			Seasonal efficiency			
Cooling	Y	Cooling	Pdesignc	2.5 kW	Cooling	SEER	10.60	A+++
Grijanje - u prosjeku	Y	Heating/Average	Pdesignh	3.0 kW	Heating/Average	SCOP(A)	5.20	A+++
Grijanje - toplije	Y	Heating/Warmer	Pdesignh	1.6 kW	Heating/Warmer	SCOP(W)	x,xx	x
Grijanje - hladnije	N	Upravljanje kapacitetom = Varijabilno						

## Cooling

Capacity				Učinkovitost		
Declared capacity for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.				Declared Energy efficiency ratio for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.		
Tj=35°C	Pdc	2.50 kW		Tj=35°C	EERd	6.32
Tj=30°C	Pdc	1.85 kW		Tj=30°C	EERd	9.30
Tj=25°C	Pdc	1.18 kW		Tj=25°C	EERd	13.45
Tj=20°C	Pdc	1.42 kW		Tj=20°C	EERd	18.80

## Grijanje (prosječna klimatska zona)

Capacity				Učinkovitost		
Declared capacity for Heating/Average season, at indoor temperature 20°C and outdoor temperature Tj.				Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj.		
Tj=-7°C	Pdh	2.65 kW		Tj=-7°C	COPd	3.30
Tj=2°C	Pdh	1.65 kW		Tj=2°C	COPd	5.40
Tj=7°C	Pdh	1.15 kW		Tj=7°C	COPd	6.50
Tj=12°C	Pdh	1.28 kW		Tj=12°C	COPd	8.45
Tj=bivalent temperature	Pdh	2.65 kW		Tj=bivalent temperature	COPd	3.30
Tj=granična radna temperatura	Pdh	2.55 kW		Tj=granična radna temperatura	COPd	2.42
Bivalentna temperatura		-7 °C				
Granične radne temperature		-15 °C				

## Heating (Warmer climate)

### Capacity

Declared capacity for Heating/Warmer at indoor temperature 20°C and outdoor temperature Tj.

### Učinkovitost

Declared coefficient of performance for Heating/Warmer climate at indoor temperature 20°C and outdoor temperature Tj.

Tj=2°C	Pdh	1.65	kW	Tj=2°C	COPd	5.40
Tj=7°C	Pdh	1.15	kW	Tj=7°C	COPd	6.50
Tj=12°C	Pdh	1.28	kW	Tj=12°C	COPd	8.45
Tj=bivalent temperature	Pdh	1.65	kW	Tj=bivalent temperature	COPd	5.40
Tj=granična radna temperatura	Pdh	2.55	kW	Tj=granična radna temperatura	COPd	2.42
Bivalentna temperatura		Tbiv	X	°C		
Granične radne temperature		Tol	X	°C		

## Electricity

Electric power input in power modes other than "on mode"

Sezonska snaga električnog priključka

Stanje isključenosti	Poff	0.001	kW	Cooling	QCE	83	kWh/a
Stanje mirovanja	Psb	0.001	kW	Heating/Average	QHE/A	807	kWh/a
Stanje isključenosti termostata	Pto	0.028	kW	Heating/Warmer	QHE/B	359	kWh/a
Način rada s grijačem kućišta	Pck	0.000	kW	Heating/Colder	QHE/C	x	kWh/a

## Radni medij

Tip		R32				
Težina				1.00	kg	
Potencijal globalnog zatopljenja	GWP			675	kgCO <sub>2</sub> eq.	

## Sound power level - db(A)

## Rated air flow - m<sup>3</sup>/h

	Cooling	Heating		Cooling	Heating
RAS-10PAVPG-E	61	62	RAS-10PAVPG-E	2160	2160
RAS-10PKVPG-E	58	59	RAS-10PKVPG-E	680	720

## Dimenzije

	Visina	Širina	Dubina	Težina
RAS-10PAVPG-E	630 mm	800 mm	300 mm	38 kg
RAS-10PKVPG-E	293 mm	851 mm	270 mm	14 kg

Harmonizirana norma

EN14511:2007, EN12102

Kontakt partner za dobivanje više informacija

Uvoznik / distributer u EU:  
Toshiba Carrier UK Ltd.  
Porsham Close, Belliver Industrial Estate,  
PLYMOUTH, Devon, PL6 7DB.  
United Kingdom

---