

## Split klima uređaj

Outdoor unit	Single inverter	RAS-16PAVPG-E
Indoor unit	DAISEIKAI 9	RAS-16PKVPG-E

Function		Design load		Seasonal efficiency
Cooling	Y	Cooling	Pdesignc	4.5 kW
Grijanje - u prosjeku	Y	Heating/Average	Pdesignh	4.5 kW
Grijanje - toplice	Y	Heating/Warmer	Pdesignh	2.5 kW
Grijanje - hladnije	N	Upravljanje kapacitetom = Varijabilno		

## Cooling

### Capacity

Declared capacity for cooling at indoor temperature 27(19)°C and outdoor temperature T<sub>j</sub>.

### Učinkovitost

Declared Energy efficiency ratio for cooling at indoor temperature 27(19)°C and outdoor temperature T<sub>j</sub>.

T <sub>j</sub> =35°C	Pdc	4.50 kW	T <sub>j</sub> =35°C	EERd	4.36
T <sub>j</sub> =30°C	Pdc	3.19 kW	T <sub>j</sub> =30°C	EERd	5.98
T <sub>j</sub> =25°C	Pdc	2.09 kW	T <sub>j</sub> =25°C	EERd	10.55
T <sub>j</sub> =20°C	Pdc	1.58 kW	T <sub>j</sub> =20°C	EERd	16.62

## Grijanje (prosječna klimatska zona)

### Capacity

Declared capacity for Heating/Average season, at indoor temperature 20°C and outdoor temperature T<sub>j</sub>.

### Učinkovitost

Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature T<sub>j</sub>.

T <sub>j</sub> =-7°C	Pdh	3.98 kW	T <sub>j</sub> =-7°C	COPd	2.83
T <sub>j</sub> =2°C	Pdh	2.47 kW	T <sub>j</sub> =2°C	COPd	4.65
T <sub>j</sub> =7°C	Pdh	1.58 kW	T <sub>j</sub> =7°C	COPd	6.04
T <sub>j</sub> =12°C	Pdh	1.31 kW	T <sub>j</sub> =12°C	COPd	7.50
T <sub>j</sub> =bivalent temperature	Pdh	3.98 kW	T <sub>j</sub> =bivalent temperature	COPd	2.83
T <sub>j</sub> =granična radna temperatura	Pdh	2.40 kW	T <sub>j</sub> =granična radna temperatura	COPd	1.80
Bivalentna temperatura		-7 °C			
Granične radne temperature		-15 °C			

## Heating (Warmer climate)

Capacity	Pdh	2.47	kW	Tj=2°C	COPd	4.65
Declared capacity for Heating/Warmer at indoor temperature 20°C and outdoor temperature Tj.				Declared coefficient of performance for Heating/Warmer climate at indoor temperature 20°C and outdoor temperature Tj.		
Tj=2°C	Pdh	2.47	kW	Tj=2°C	COPd	4.65
Tj=7°C	Pdh	1.58	kW	Tj=7°C	COPd	6.04
Tj=12°C	Pdh	1.31	kW	Tj=12°C	COPd	7.50
Tj=bivalent temperature	Pdh	2.47	kW	Tj=bivalent temperature	COPd	4.65
Tj=granična radna temperatura	Pdh	2.40	kW	Tj=granična radna temperatura	COPd	1.80
Bivalentna temperatura	Tbiv	X	°C			
Granične radne temperature	Tol	X	°C			

## Electricity

Electric power input in power modes other than "on mode"				Sezonska snaga električnog priključka			
Stanje isključenosti	Poff	0.001	kW	Cooling	QCE	185	kWh/a
Stanje mirovanja	Psb	0.001	kW	Heating/Average	QHE/A	1369	kWh/a
Stanje isključenosti termostata	Pto	0.029	kW	Heating/Warmer	QHE/B	584	kWh/a
Način rada s grijačem kućišta	Pck	0.000	kW	Heating/Colder	QHE/C	x	kWh/a

## Radni medij

Tip	R32
Težina	1.00 kg
Potencijal globalnog zatopljenja	675 kgCO <sub>2</sub> eq.

## Sound power level - db(A)

## Rated air flow - m<sup>3</sup>/h

	Cooling	Heating		Cooling	Heating
RAS-16PAVPG-E	64	65	RAS-16PAVPG-E	2160	2160
RAS-16PKVPG-E	60	61	RAS-16PKVPG-E	730	740

## Dimenzije

	Visina	Širina	Dubina	Težina
RAS-16PAVPG-E	630 mm	800 mm	300 mm	38 kg
RAS-16PKVPG-E	293 mm	851 mm	270 mm	14 kg

Uvoznik / distributer u EU:  
Toshiba Carrier UK Ltd.  
Kontakt partner za dobivanje više informacija  
Porsham Close, Belliver Industrial Estate,  
PLYMOUTH, Devon, PL6 7DB.  
United Kingdom

---