

## Split klima uređaj

Outdoor unit	Single inverter	RAS-10PAVSG-E
Indoor unit	Console	RAS-B10U2FVG-E1

Function		Design load		Seasonal efficiency
Cooling	Y	Cooling	Pdesignc	2.5 kW
Grijanje - u prosjeku	Y	Heating/Average	Pdesignh	2.5 kW
Grijanje - toplice	Y	Heating/Warmer	Pdesignh	1.4 kW
Grijanje - hladnije	N	Upravljanje kapacitetom = Varijabilno		

## Cooling

Capacity	Učinkovitost
Declared capacity for cooling at indoor temperature 27(19)°C and outdoor temperature T <sub>j</sub> .	Declared Energy efficiency ratio for cooling at indoor temperature 27(19)°C and outdoor temperature T <sub>j</sub> .
T <sub>j</sub> =35°C	Pdc
2.54 kW	T <sub>j</sub> =35°C
T <sub>j</sub> =30°C	Pdc
1.81 kW	T <sub>j</sub> =30°C
T <sub>j</sub> =25°C	Pdc
1.15 kW	T <sub>j</sub> =25°C
T <sub>j</sub> =20°C	Pdc
0.97 kW	T <sub>j</sub> =20°C

## Grijanje (prosječna klimatska zona)

Capacity	Učinkovitost
Declared capacity for Heating/Average season, at indoor temperature 20°C and outdoor temperature T <sub>j</sub> .	Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature T <sub>j</sub> .
T <sub>j</sub> =-7°C	Pdh
2.19 kW	T <sub>j</sub> =-7°C
T <sub>j</sub> =2°C	Pdh
1.36 kW	T <sub>j</sub> =2°C
T <sub>j</sub> =7°C	Pdh
0.93 kW	T <sub>j</sub> =7°C
T <sub>j</sub> =12°C	Pdh
0.91 kW	T <sub>j</sub> =12°C
T <sub>j</sub> =bivalent temperature	Pdh
2.21 kW	T <sub>j</sub> =bivalent temperature
T <sub>j</sub> =granična radna temperatura	Pdh
1.70 kW	T <sub>j</sub> =granična radna temperatura
Bivalentna temperatura	-7 °C
Granične radne temperature	-15 °C

## Heating (Warmer climate)

### Capacity

Declared capacity for Heating/Warmer at indoor temperature 20°C and outdoor temperature Tj.

### Učinkovitost

Declared coefficient of performance for Heating/Warmer climate at indoor temperature 20°C and outdoor temperature Tj.

Tj=2°C	Pdh	1.36	kW	Tj=2°C	COPd	4.32
Tj=7°C	Pdh	0.93	kW	Tj=7°C	COPd	5.43
Tj=12°C	Pdh	0.91	kW	Tj=12°C	COPd	6.45
Tj=bivalent temperature	Pdh	1.35	kW	Tj=bivalent temperature	COPd	2.59
Tj=granična radna temperatura	Pdh	1.70	kW	Tj=granična radna temperatura	COPd	2.10
Bivalentna temperatura	Tbiv			X °C		
Granične radne temperature	Tol			X °C		

## Electricity

### Electric power input in power modes other than "on mode"

### Sezonska snaga električnog priključka

Stanje isključenosti	Poff	0.001	kW	Cooling	QCE	133	kWh/a
Stanje mirovanja	Psb	0.001	kW	Heating/Average	QHE/A	833	kWh/a
Stanje isključenosti termostata	Pto	0.029	kW	Heating/Warmer	QHE/B	373	kWh/a
Način rada s grijajućem kućišta	Pck	0.000	kW	Heating/Colder	QHE/C	x	kWh/a

## Radni medij

Tip	R32
Težina	0.51 kg
Potencijal globalnog zatopljenja	675 kgCO <sub>2</sub> eq.

## Sound power level - db(A)

## Rated air flow - m<sup>3</sup>/h

	Cooling	Heating		Cooling	Heating
RAS-10PAVSG-E	61	62	RAS-10PAVSG-E	1660	1660
RAS-B10U2FVG-E1	54	54	RAS-B10U2FVG-E1	460	510

## Dimenzije

	Visina	Širina	Dubina	Težina
RAS-10PAVSG-E	550 mm	780 mm	290 mm	28 kg
RAS-B10U2FVG-E1	600 mm	700 mm	220 mm	16 kg

Uvoznik / distributer u EU:  
Toshiba Carrier UK Ltd.  
Kontakt partner za dobivanje više informacija  
Porsham Close, Belliver Industrial Estate,  
PLYMOUTH, Devon, PL6 7DB.  
United Kingdom

---