

Split klima uređaj

Outdoor unit	Single inverter	RAV-GM301ATP-E
Indoor unit	Compact 4-way Cassette	RAV-RM301MUT-E

Function		Design load			Seasonal efficiency			
Cooling	Y	Cooling	Pdesignc	2.5 kW	Cooling	SEER	5.94	A+
Grijanje - u prosjeku	Y	Heating/Average	Pdesignh	2.3 kW	Heating/Average	SCOP(A)	4.70	A++
Grijanje - toplije	N	Upravljanje kapacitetom = Varijabilno						
Grijanje - hladnije	N							

Cooling

Capacity			Učinkovitost		
Declared capacity for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.			Declared Energy efficiency ratio for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.		
Tj=35°C	Pdc	2.50 kW	Tj=35°C	EERd	4.24
Tj=30°C	Pdc	1.84 kW	Tj=30°C	EERd	5.89
Tj=25°C	Pdc	1.18 kW	Tj=25°C	EERd	8.92
Tj=20°C	Pdc	1.04 kW	Tj=20°C	EERd	11.14

Grijanje (prosječna klimatska zona)

Capacity			Učinkovitost		
Declared capacity for Heating/Average season, at indoor temperature 20°C and outdoor temperature Tj.			Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj.		
Tj=-7°C	Pdh	2.03 kW	Tj=-7°C	COPd	3.10
Tj=2°C	Pdh	1.24 kW	Tj=2°C	COPd	4.73
Tj=7°C	Pdh	0.82 kW	Tj=7°C	COPd	5.93
Tj=12°C	Pdh	0.89 kW	Tj=12°C	COPd	7.80
Tj=bivalent temperature	Pdh	2.03 kW	Tj=bivalent temperature	COPd	3.10
Tj=granična radna temperatura	Pdh	1.81 kW	Tj=granična radna temperatura	COPd	2.02
Bivalentna temperatura		-7 °C			
Granične radne temperature		-15 °C			

Electricity

Electric power input in power modes other than "on mode"

Sezonska snaga električnog priključka

Stanje isključenosti	Poff	0.012	kW	Cooling	QCE	147	kWh/a
Stanje mirovanja	Psb	0.012	kW	Heating/Average	QHE/A	685	kWh/a
Stanje isključenosti termostata	Pto	0.030	kW	Heating/Warmer	QHE/B	x	kWh/a
Način rada s grijačem kućišta	Pck	0.000	kW	Heating/Colder	QHE/C	x	kWh/a

Radni medij

Tip	R32		
Težina	0.63 kg		
Potencijal globalnog zatopljenja	GWP	675 kgCO ₂ eq.	

Sound power level - db(A)

Rated air flow - m³/h

	Cooling	Heating		Cooling	Heating
RAV-GM301ATP-E	61	62	RAV-GM301ATP-E	1800	1800
RAV-RM301MUT-E	53	53	RAV-RM301MUT-E	640	640

Dimenzije

	Visina	Širina	Dubina	Težina
RAV-GM301ATP-E	550 mm	780 mm	290 mm	29 kg
RAV-RM301MUT-E	256 mm	575 mm	575 mm	15 kg

Harmonizirana norma	EN14511:2007, EN12102
---------------------	-----------------------

Metode obračuna - mjerne norme	PrEN 14825: 2011 Sekcija 8 i 9
--------------------------------	--------------------------------

Kontakt partner za dobivanje više informacija	Uvoznik / distributer u EU: Toshiba Carrier UK Ltd. Porsham Close, Belliver Industrial Estate, PLYMOUTH, Devon, PL6 7DB. United Kingdom
---	---