

## Split klima uređaj

Outdoor unit	Single inverter	RAV-GM301ATP-E
Indoor unit	Slim Duct	RAV-RM301SDT-E

Function		Design load			Seasonal efficiency			
Cooling	Y	Cooling	Pdesignc	2.5 kW	Cooling	SEER	6.29	A++
Grijanje - u prosjeku	Y	Heating/Average	Pdesignh	2.6 kW	Heating/Average	SCOP(A)	4.60	A++
Grijanje - toplije	N	Upravljanje kapacitetom = Varijabilno						
Grijanje - hladnije	N							

## Cooling

Capacity				Učinkovitost			
Declared capacity for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.				Declared Energy efficiency ratio for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.			
Tj=35°C	Pdc	2.50	kW	Tj=35°C	EERd		4.46
Tj=30°C	Pdc	1.84	kW	Tj=30°C	EERd		6.21
Tj=25°C	Pdc	1.18	kW	Tj=25°C	EERd		9.41
Tj=20°C	Pdc	1.09	kW	Tj=20°C	EERd		12.38

## Grijanje (prosječna klimatska zona)

Capacity				Učinkovitost			
Declared capacity for Heating/Average season, at indoor temperature 20°C and outdoor temperature Tj.				Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj.			
Tj=-7°C	Pdh	2.30	kW	Tj=-7°C	COPd		3.03
Tj=2°C	Pdh	1.40	kW	Tj=2°C	COPd		4.60
Tj=7°C	Pdh	1.00	kW	Tj=7°C	COPd		5.89
Tj=12°C	Pdh	1.16	kW	Tj=12°C	COPd		7.70
Tj=bivalent temperature	Pdh	2.30	kW	Tj=bivalent temperature	COPd		2.89
Tj=granična radna temperatura	Pdh	2.63	kW	Tj=granična radna temperatura	COPd		2.58
Bivalentna temperatura		-7	°C				
Granične radne temperature		-15	°C				

## Electricity

Electric power input in power modes other than "on mode"

Sezonska snaga električnog priključka

Stanje isključenosti	Poff	0.012	kW	Cooling	QCE	139	kWh/a
Stanje mirovanja	Psb	0.012	kW	Heating/Average	QHE/A	791	kWh/a
Stanje isključenosti termostata	Pto	0.024	kW	Heating/Warmer	QHE/B	x	kWh/a
Način rada s grijačem kućišta	Pck	0.000	kW	Heating/Colder	QHE/C	x	kWh/a

## Radni medij

Tip	R32		
Težina	0.63 kg		
Potencijal globalnog zatopljenja	GWP	675 kgCO <sub>2</sub> eq.	

## Sound power level - db(A)

## Rated air flow - m<sup>3</sup>/h

	Cooling	Heating		Cooling	Heating
RAV-GM301ATP-E	61	62	RAV-GM301ATP-E	1800	1800
RAV-RM301SDT-E	54	54	RAV-RM301SDT-E	660	660

## Dimenzije

	Visina	Širina	Dubina	Težina
RAV-GM301ATP-E	550 mm	780 mm	290 mm	29 kg
RAV-RM301SDT-E	210 mm	845 mm	645 mm	22 kg

Harmonizirana norma EN14511:2007 , EN12102

Metode obračuna - mjerne norme PrEN 14825: 2011 Sekcija 8 i 9

Kontakt partner za dobivanje više informacija

Uvoznik / distributer u EU:  
Toshiba Carrier UK Ltd.  
Porsham Close, Belliver Industrial Estate,  
PLYMOUTH, Devon, PL6 7DB.  
United Kingdom