

## Split klima uređaj

Outdoor unit	Single inverter	RAV-GM401ATP-E
Indoor unit	Hi-wall Bi Refrigerant - R32 R410A	RAV-RM401KRTP-E

Function		Design load			Seasonal efficiency			
Cooling	Y	Cooling	Pdesignc	3.6 kW	Cooling	SEER	6.12	A++
Grijanje - u prosjeku	Y	Heating/Average	Pdesignh	2.7 kW	Heating/Average	SCOP(A)	4.22	A+
Grijanje - toplije	N	Upravljanje kapacitetom = Varijabilno						
Grijanje - hladnije	N							

## Cooling

Capacity				Učinkovitost			
Declared capacity for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.				Declared Energy efficiency ratio for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.			
Tj=35°C	Pdc	3.60 kW		Tj=35°C	EERd		3.19
Tj=30°C	Pdc	2.65 kW		Tj=30°C	EERd		5.58
Tj=25°C	Pdc	1.71 kW		Tj=25°C	EERd		8.10
Tj=20°C	Pdc	1.76 kW		Tj=20°C	EERd		11.25

## Grijanje (prosječna klimatska zona)

Capacity				Učinkovitost			
Declared capacity for Heating/Average season, at indoor temperature 20°C and outdoor temperature Tj.				Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj.			
Tj=-7°C	Pdh	2.39 kW		Tj=-7°C	COPd		2.94
Tj=2°C	Pdh	1.45 kW		Tj=2°C	COPd		4.17
Tj=7°C	Pdh	0.93 kW		Tj=7°C	COPd		5.24
Tj=12°C	Pdh	1.12 kW		Tj=12°C	COPd		6.92
Tj=bivalent temperature	Pdh	2.39 kW		Tj=bivalent temperature	COPd		2.94
Tj=granična radna temperatura	Pdh	2.10 kW		Tj=granična radna temperatura	COPd		2.26
Bivalentna temperatura		-7 °C					
Granične radne temperature		-15 °C					

## Electricity

Electric power input in power modes other than "on mode"

Sezonska snaga električnog priključka

Stanje isključenosti	Poff	0.009	kW	Cooling	QCE	206	kWh/a
Stanje mirovanja	Psb	0.009	kW	Heating/Average	QHE/A	895	kWh/a
Stanje isključenosti termostata	Pto	0.024	kW	Heating/Warmer	QHE/B	x	kWh/a
Način rada s grijačem kućišta	Pck	0.000	kW	Heating/Colder	QHE/C	x	kWh/a

## Radni medij

Tip	R32		
Težina	0.90 kg		
Potencijal globalnog zatopljenja	GWP	675 kgCO <sub>2</sub> eq.	

## Sound power level - db(A)

## Rated air flow - m<sup>3</sup>/h

	Cooling	Heating		Cooling	Heating
RAV-GM401ATP-E	64	65	RAV-GM401ATP-E	2200	2200
RAV-RM401KRTP-E	56	56	RAV-RM401KRTP-E	700	700

## Dimenzije

	Visina	Širina	Dubina	Težina
RAV-GM401ATP-E	550 mm	780 mm	290 mm	34 kg
RAV-RM401KRTP-E	293 mm	798 mm	290 mm	10 kg

Harmonizirana norma EN14511:2007, EN12102

Metode obračuna - mjerne norme PrEN 14825: 2011 Sekcija 8 i 9

Kontakt partner za dobivanje više informacija

Uvoznik / distributer u EU:  
Toshiba Carrier UK Ltd.  
Porsham Close, Belliver Industrial Estate,  
PLYMOUTH, Devon, PL6 7DB.  
United Kingdom