

**PRODUCT INFORMATION (\*)**

ROOM AIR CONDITIONER	INDOOR MODEL OUTDOOR MODEL	MSZ-HJ35VA MUS-HJ35VA
----------------------	-------------------------------	--------------------------

Function (Indicate if present)	
cooling	Y
heating	Y

If function includes heating: Indicate the heating season the information relates to. Indicated values should relate to one heating season at a time. Include at least the heating season			
Average (mandatory)	Y		
Warmer (if designated)	Y		
Colder (if designated)	N		

Item	symbol	value	unit
Design load			
cooling	Pdesignc	3.1	kW
heating/Average	Pdesignh	2.4	kW
heating/Warmer	Pdesignh	1.3	kW
heating/Colder	Pdesignh	x	kW

Item	symbol	value	unit
Seasonal efficiency			
cooling	SEER	5.1	-
heating/Average	SCOP/A	3.8	-
heating/Warmer	SCOP/W	4.3	-
heating/Colder	SCOP/C	x	-

Declared capacity for cooling, at indoor temperature 27(19)°C and outdoor temperature Tj			
Tj=35°C	Pdc	3.1	kW
Tj=30°C	Pdc	2.3	kW
Tj=25°C	Pdc	2.0	kW
Tj=20°C	Pdc	1.8	kW

Declared energy efficiency ratio, at indoor temperature 27(19)°C and outdoor temperature Tj			
Tj=35°C	EERd	3.0	-
Tj=30°C	EERd	4.5	-
Tj=25°C	EERd	6.3	-
Tj=20°C	EERd	7.5	-

Declared capacity for heating/Average season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=-7°C	Pdh	2.2	kW
Tj=2°C	Pdh	1.3	kW
Tj=7°C	Pdh	1.5	kW
Tj=12°C	Pdh	1.7	kW
Tj=bivalent temperature	Pdh	2.4	kW
Tj=operating limit	Pdh	2.4	kW

Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=-7°C	COPd	2.8	-
Tj=2°C	COPd	3.9	-
Tj=7°C	COPd	4.8	-
Tj=12°C	COPd	5.6	-
Tj=bivalent temperature	COPd	2.4	-
Tj=operating limit	COPd	2.4	-

Declared capacity for heating/Warmer season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=2°C	Pdh	1.3	kW
Tj=7°C	Pdh	1.5	kW
Tj=12°C	Pdh	1.7	kW
Tj=bivalent temperature	Pdh	1.3	kW
Tj=operating limit	Pdh	2.4	kW

Declared coefficient of performance/Warmer season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=2°C	COPd	3.9	-
Tj=7°C	COPd	4.8	-
Tj=12°C	COPd	5.6	-
Tj=bivalent temperature	COPd	3.9	-
Tj=operating limit	COPd	2.4	-

Declared capacity for heating/Colder season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=-7°C	Pdh	x	kW
Tj=2°C	Pdh	x	kW
Tj=7°C	Pdh	x	kW
Tj=12°C	Pdh	x	kW
Tj=bivalent temperature	Pdh	x	kW
Tj=operating limit	Pdh	x	kW
Tj=-15°C	Pdh	x	kW

Declared coefficient of performance/Colder season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=-7°C	COPd	x	-
Tj=2°C	COPd	x	-
Tj=7°C	COPd	x	-
Tj=12°C	COPd	x	-
Tj=bivalent temperature	COPd	x	-
Tj=operating limit	COPd	x	-
Tj=-15°C	COPd	x	-

Bivalent temperature			
heating/Average	Tbiv	-10	°C
heating/Warmer	Tbiv	x	°C
heating/Colder	Tbiv	x	°C

Operating limit temperature			
heating/Average	Tol	-10	°C
heating/Warmer	Tol	x	°C
heating/Colder	Tol	x	°C

Cycling interval capacity			
for cooling	Pcyc	x	kW
for heating	Pchc	x	kW
Degradation co-efficient	Cdc	0.25	-

Cycling interval efficiency			
for cooling	EERcyc	x	-
for heating	COPcyc	x	-
Degradation co-efficient	Cdh	0.25	-

Electric power input in power modes other than 'active mode'			
off mode	Poff	1	W
standby mode	Pss	1	W
thermostat - off mode	Pto	12	W
crankcase heater mode	Pck	0	W

Annual electricity consumption			
cooling	Qce	212	kWh/a
heating/Average	Qhe	885	kWh/a
heating/Warmer	Qhe	426	kWh/a
heating/Colder	Qhe	x	kWh/a

Capacity control (Indicate one of three options)			
fixed		N	
slaged		N	
variable		Y	

Other items			
Sound power level (indoor/outdoor)	Lwa	60/64	dB(A)
Global warming potential	GWP	1975	kgCO <sub>2</sub> eq
Rated air flow (indoor/outdoor)	-	654/1890	m <sup>3</sup> /h

Contact details for obtaining more information	MITSUBISHI ELECTRIC CORPORATION SHIZUOKA WORKS 3-18-1, Oshika, Suruga-ku, Shizuoka 422-8528, Japan E-mail: melsherp@MitsubishiElectric.co.jp
--	--

(\*) This information is based on the "product information requirement" in COMMISSION REGULATION (EU) No206/2012.