

## Split klima uređaj

Outdoor unit	Single inverter	RAV-GM1101AT8P-E
Indoor unit	Ceiling	RAV-RM1101CTP-E

Function		Design load			Seasonal efficiency			
Cooling	Y	Cooling	Pdesignc	9.5 kW	Cooling	SEER	5.86	A+
Grijanje - u prosjeku	Y	Heating/Average	Pdesignh	7.6 kW	Heating/Average	SCOP(A)	4.27	A+
Grijanje - toplije	N	Upravljanje kapacitetom = Varijabilno						
Grijanje - hladnije	N							

## Cooling

Capacity				Učinkovitost			
Declared capacity for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.				Declared Energy efficiency ratio for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.			
Tj=35°C	Pdc	9.50	kW	Tj=35°C	EERd	3.22	
Tj=30°C	Pdc	7.00	kW	Tj=30°C	EERd	4.94	
Tj=25°C	Pdc	4.50	kW	Tj=25°C	EERd	7.05	
Tj=20°C	Pdc	4.00	kW	Tj=20°C	EERd	11.23	

## Grijanje (prosječna klimatska zona)

Capacity				Učinkovitost			
Declared capacity for Heating/Average season, at indoor temperature 20°C and outdoor temperature Tj.				Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj.			
Tj=-7°C	Pdh	6.72	kW	Tj=-7°C	COPd	2.66	
Tj=2°C	Pdh	4.09	kW	Tj=2°C	COPd	4.33	
Tj=7°C	Pdh	2.85	kW	Tj=7°C	COPd	5.64	
Tj=12°C	Pdh	3.03	kW	Tj=12°C	COPd	6.80	
Tj=bivalent temperature	Pdh	6.72	kW	Tj=bivalent temperature	COPd	2.66	
Tj=granična radna temperatura	Pdh	4.57	kW	Tj=granična radna temperatura	COPd	1.60	
Bivalentna temperatura		-7	°C				
Granične radne temperature		-15	°C				

## Electricity

Electric power input in power modes other than "on mode"

Sezonska snaga električnog priključka

Stanje isključenosti	Poff	0.014 kW	Cooling	QCE	567 kWh/a
Stanje mirovanja	Psb	0.014 kW	Heating/Average	QHE/A	2490 kWh/a
Stanje isključenosti termostata	Pto	0.078 kW	Heating/Warmer	QHE/B	x kWh/a
Način rada s grijačem kućišta	Pck	0.000 kW	Heating/Colder	QHE/C	x kWh/a

## Radni medij

Tip	R32				
Težina	2.10 kg				
Potencijal globalnog zatopljenja	GWP	675 kgCO <sub>2</sub> eq.			

## Sound power level - db(A)

## Rated air flow - m<sup>3</sup>/h

	Cooling	Heating		Cooling	Heating
RAV-GM1101AT8P-E	70	74	RAV-GM1101AT8P-E	4080	4080
RAV-RM1101CTP-E	59	59	RAV-RM1101CTP-E	1860	1860

## Dimenzije

	Visina	Širina	Dubina	Težina
RAV-GM1101AT8P-E	890 mm	900 mm	320 mm	68 kg
RAV-RM1101CTP-E	235 mm	1586 mm	690 mm	37 kg

Harmonizirana norma EN14511:2007 , EN12102

Metode obračuna - mjerne norme PrEN 14825: 2011 Sekcija 8 i 9

Kontakt partner za dobivanje više informacija

Uvoznik / distributer u EU:  
Toshiba Carrier UK Ltd.  
Porsham Close, Belliver Industrial Estate,  
PLYMOUTH, Devon, PL6 7DB.  
United Kingdom