

## Split klima uređaj

Outdoor unit	Single inverter	RAV-GP1101AT-E
Indoor unit	Ceiling	RAV-RM1101CTP-E

Function		Design load			Seasonal efficiency			
Cooling	Y	Cooling	Pdesignc	10.0 kW	Cooling	SEER	8.23	A++
Grijanje - u prosjeku	Y	Heating/Average	Pdesignh	9.2 kW	Heating/Average	SCOP(A)	4.72	A++
Grijanje - toplije	N	Upravljanje kapacitetom = Varijabilno						
Grijanje - hladnije	N							

## Cooling

Capacity				Učinkovitost			
Declared capacity for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.				Declared Energy efficiency ratio for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.			
Tj=35°C	Pdc	10.00	kW	Tj=35°C	EERd		4.48
Tj=30°C	Pdc	7.27	kW	Tj=30°C	EERd		6.11
Tj=25°C	Pdc	4.72	kW	Tj=25°C	EERd		10.73
Tj=20°C	Pdc	3.63	kW	Tj=20°C	EERd		15.78

## Grijanje (prosječna klimatska zona)

Capacity				Učinkovitost			
Declared capacity for Heating/Average season, at indoor temperature 20°C and outdoor temperature Tj.				Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj.			
Tj=-7°C	Pdh	8.14	kW	Tj=-7°C	COPd		3.12
Tj=2°C	Pdh	4.96	kW	Tj=2°C	COPd		4.72
Tj=7°C	Pdh	3.21	kW	Tj=7°C	COPd		6.06
Tj=12°C	Pdh	3.07	kW	Tj=12°C	COPd		7.68
Tj=bivalent temperature	Pdh	8.14	kW	Tj=bivalent temperature	COPd		3.12
Tj=granična radna temperatura	Pdh	1.63	kW	Tj=granična radna temperatura	COPd		0.92
Bivalentna temperatura		-7	°C				
Granične radne temperature		-27	°C				

## Electricity

Electric power input in power modes other than "on mode"

Sezonska snaga električnog priključka

Stanje isključenosti	Poff	0.007	kW	Cooling	QCE	425	kWh/a
Stanje mirovanja	Psb	0.007	kW	Heating/Average	QHE/A	2726	kWh/a
Stanje isključenosti termostata	Pto	0.086	kW	Heating/Warmer	QHE/B	x	kWh/a
Način rada s grijačem kućišta	Pck	0.000	kW	Heating/Colder	QHE/C	x	kWh/a

## Radni medij

Tip				R32			
Težina				3.10	kg		
Potencijal globalnog zatopljenja	GWP			675	kgCO <sub>2</sub> eq.		

## Sound power level - db(A)

## Rated air flow - m<sup>3</sup>/h

	Cooling	Heating		Cooling	Heating
RAV-GP1101AT-E	66	67	RAV-GP1101AT-E	6960	6960
RAV-RM1101CTP-E	59	59	RAV-RM1101CTP-E	1860	1860

## Dimenzije

	Visina	Širina	Dubina	Težina
RAV-GP1101AT-E	1550 mm	1010 mm	370 mm	104 kg
RAV-RM1101CTP-E	235 mm	1586 mm	690 mm	37 kg

Harmonizirana norma EN14511:2007 , EN12102

Metode obračuna - mjerne norme PrEN 14825: 2011 Sekcija 8 i 9

Kontakt partner za dobivanje više informacija

Uvoznik / distributer u EU:  
Toshiba Carrier UK Ltd.  
Porsham Close, Belliver Industrial Estate,  
PLYMOUTH, Devon, PL6 7DB.  
United Kingdom