

## Split klima uređaj

Outdoor unit	Single inverter	RAV-GM1101ATP-E
Indoor unit	4-way Cassette	RAV-RM1101UTP-E

### Function

Cooling	Y
Grijanje - u prosjeku	Y
Grijanje - toplije	N
Grijanje - hladnije	N

### Design load

Cooling	Pdesignc	9.5 kW
Heating/Average	Pdesignh	8.0 kW

Upravljanje kapacitetom = Varijabilno

### Seasonal efficiency

Cooling	SEER	6.15	A++
Heating/Average	SCOP(A)	4.28	A+

## Cooling

#### Capacity

Declared capacity for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.

#### Učinkovitost

Declared Energy efficiency ratio for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.

Tj=35°C	Pdc	9.50 kW	Tj=35°C	EERd	3.31
Tj=30°C	Pdc	7.00 kW	Tj=30°C	EERd	5.43
Tj=25°C	Pdc	4.50 kW	Tj=25°C	EERd	7.50
Tj=20°C	Pdc	4.25 kW	Tj=20°C	EERd	11.58

## Grijanje (prosječna klimatska zona)

#### Capacity

Declared capacity for Heating/Average season, at indoor temperature 20°C and outdoor temperature Tj.

#### Učinkovitost

Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj.

Tj=-7°C	Pdh	7.08 kW	Tj=-7°C	COPd	2.74
Tj=2°C	Pdh	4.31 kW	Tj=2°C	COPd	4.33
Tj=7°C	Pdh	2.77 kW	Tj=7°C	COPd	5.58
Tj=12°C	Pdh	3.26 kW	Tj=12°C	COPd	6.67
Tj=bivalent temperature	Pdh	7.08 kW	Tj=bivalent temperature	COPd	2.74
Tj=granična radna temperatura	Pdh	4.81 kW	Tj=granična radna temperatura	COPd	1.60
Bivalentna temperatura		-7 °C			
Granične radne temperature		-15 °C			

## Electricity

Electric power input in power modes other than "on mode"

Sezonska snaga električnog priključka

Stanje isključenosti	Poff	0.016	kW	Cooling	QCE	540	kWh/a
Stanje mirovanja	Psb	0.016	kW	Heating/Average	QHE/A	2615	kWh/a
Stanje isključenosti termostata	Pto	0.073	kW	Heating/Warmer	QHE/B	x	kWh/a
Način rada s grijačem kućišta	Pck	0.000	kW	Heating/Colder	QHE/C	x	kWh/a

## Radni medij

Tip	R32		
Težina	2.10 kg		
Potencijal globalnog zatopljenja	GWP	675 kgCO <sub>2</sub> eq.	

## Sound power level - db(A)

## Rated air flow - m<sup>3</sup>/h

	Cooling	Heating		Cooling	Heating
RAV-GM1101ATP-E	70	74	RAV-GM1101ATP-E	4080	4080
RAV-RM1101UTP-E	58	58	RAV-RM1101UTP-E	2010	2010

## Dimenzije

	Visina	Širina	Dubina	Težina
RAV-GM1101ATP-E	890 mm	900 mm	320 mm	68 kg
RAV-RM1101UTP-E	319 mm	840 mm	840 mm	24 kg

Harmonizirana norma EN14511:2007 , EN12102

Metode obračuna - mjerne norme PrEN 14825: 2011 Sekcija 8 i 9

Kontakt partner za dobivanje više informacija  
 Uvoznik / distributer u EU:  
 Toshiba Carrier UK Ltd.  
 Porsham Close, Belliver Industrial Estate,  
 PLYMOUTH, Devon, PL6 7DB.  
 United Kingdom