

Split klima uređaj

Outdoor unit	Single inverter	RAV-GM401ATP-E
Indoor unit	Slim Duct	RAV-RM401SDT-E

Function

Design load

Seasonal efficiency

Cooling	Y	Cooling	Pdesignc	3.6 kW	Cooling	SEER	5.86	A+
Grijanje - u prosjeku	Y	Heating/Average	Pdesignh	2.7 kW	Heating/Average	SCOP(A)	4.01	A+
Grijanje - toplije	N	Upravljanje kapacitetom = Varijabilno						
Grijanje - hladnije	N							

Cooling

Capacity

Declared capacity for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.

Učinkovitost

Declared Energy efficiency ratio for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.

Tj=35°C	Pdc	3.60 kW	Tj=35°C	EERd	3.87
Tj=30°C	Pdc	2.65 kW	Tj=30°C	EERd	5.60
Tj=25°C	Pdc	1.71 kW	Tj=25°C	EERd	7.64
Tj=20°C	Pdc	1.28 kW	Tj=20°C	EERd	9.95

Grijanje (prosječna klimatska zona)

Capacity

Declared capacity for Heating/Average season, at indoor temperature 20°C and outdoor temperature Tj.

Učinkovitost

Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj.

Tj=-7°C	Pdh	2.39 kW	Tj=-7°C	COPd	2.66
Tj=2°C	Pdh	1.45 kW	Tj=2°C	COPd	3.96
Tj=7°C	Pdh	1.02 kW	Tj=7°C	COPd	5.17
Tj=12°C	Pdh	1.12 kW	Tj=12°C	COPd	6.49
Tj=bivalent temperature	Pdh	2.39 kW	Tj=bivalent temperature	COPd	2.66
Tj=granična radna temperatura	Pdh	2.20 kW	Tj=granična radna temperatura	COPd	1.83
Bivalentna temperatura		-7 °C			
Granične radne temperature		-15 °C			

Electricity

Electric power input in power modes other than "on mode"

Sezonska snaga električnog priključka

Stanje isključenosti	Poff	0.012	kW	Cooling	QCE	215	kWh/a
Stanje mirovanja	Psb	0.012	kW	Heating/Average	QHE/A	943	kWh/a
Stanje isključenosti termostata	Pto	0.024	kW	Heating/Warmer	QHE/B	x	kWh/a
Način rada s grijačem kućišta	Pck	0.000	kW	Heating/Colder	QHE/C	x	kWh/a

Radni medij

Tip	R32		
Težina	0.90 kg		
Potencijal globalnog zatopljenja	GWP	675 kgCO ₂ eq.	

Sound power level - db(A)

Rated air flow - m³/h

	Cooling	Heating		Cooling	Heating
RAV-GM401ATP-E	64	65	RAV-GM401ATP-E	2200	2200
RAV-RM401SDT-E	54	54	RAV-RM401SDT-E	690	690

Dimenzije

	Visina	Širina	Dubina	Težina
RAV-GM401ATP-E	550 mm	780 mm	290 mm	34 kg
RAV-RM401SDT-E	210 mm	845 mm	645 mm	22 kg

Harmonizirana norma EN14511:2007 , EN12102

Metode obračuna - mjerne norme PrEN 14825: 2011 Sekcija 8 i 9

Kontakt partner za dobivanje više informacija

Uvoznik / distributer u EU:
Toshiba Carrier UK Ltd.
Porsham Close, Belliver Industrial Estate,
PLYMOUTH, Devon, PL6 7DB.
United Kingdom