

Split klima uređaj

Outdoor unit	Single inverter	RAV-GP561ATP-E
Indoor unit	Hi-wall Bi Refrigerant - R32 R410A	RAV-RM561KRTP-E

Function		Design load			Seasonal efficiency			
Cooling	Y	Cooling	Pdesignc	5.0 kW	Cooling	SEER	7.59	A++
Grijanje - u prosjeku	Y	Heating/Average	Pdesignh	3.8 kW	Heating/Average	SCOP(A)	4.17	A+
Grijanje - toplije	N	Upravljanje kapacitetom = Varijabilno						
Grijanje - hladnije	N							

Cooling

Capacity			Učinkovitost		
Declared capacity for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.			Declared Energy efficiency ratio for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.		
Tj=35°C	Pdc	5.00 kW	Tj=35°C	EERd	3.50
Tj=30°C	Pdc	3.68 kW	Tj=30°C	EERd	5.90
Tj=25°C	Pdc	2.37 kW	Tj=25°C	EERd	10.67
Tj=20°C	Pdc	1.05 kW	Tj=20°C	EERd	15.13

Grijanje (prosječna klimatska zona)

Capacity			Učinkovitost		
Declared capacity for Heating/Average season, at indoor temperature 20°C and outdoor temperature Tj.			Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj.		
Tj=-7°C	Pdh	3.36 kW	Tj=-7°C	COPd	2.74
Tj=2°C	Pdh	2.05 kW	Tj=2°C	COPd	4.22
Tj=7°C	Pdh	1.32 kW	Tj=7°C	COPd	5.15
Tj=12°C	Pdh	0.58 kW	Tj=12°C	COPd	6.10
Tj=bivalent temperature	Pdh	3.36 kW	Tj=bivalent temperature	COPd	2.74
Tj=granična radna temperatura	Pdh	0.67 kW	Tj=granična radna temperatura	COPd	0.80
Bivalentna temperatura		-7 °C			
Granične radne temperature		-27 °C			

Electricity

Electric power input in power modes other than "on mode"

Sezonska snaga električnog priključka

Stanje isključenosti	Poff	0.009	kW	Cooling	QCE	230	kWh/a
Stanje mirovanja	Psb	0.009	kW	Heating/Average	QHE/A	1274	kWh/a
Stanje isključenosti termostata	Pto	0.040	kW	Heating/Warmer	QHE/B	x	kWh/a
Način rada s grijanjem kućišta	Pck	0.000	kW	Heating/Colder	QHE/C	x	kWh/a

Radni medij

Tip	R32		
Težina	1.35 kg		
Potencijal globalnog zatopljenja	GWP	675 kgCO ₂ eq.	

Sound power level - db(A)

Rated air flow - m³/h

	Cooling	Heating		Cooling	Heating
RAV-GP561ATP-E	63	65	RAV-GP561ATP-E	2250	2070
RAV-RM561KRTP-E	57	57	RAV-RM561KRTP-E	960	960

Dimenzije

	Visina	Širina	Dubina	Težina
RAV-GP561ATP-E	630 mm	799 mm	299 mm	45 kg
RAV-RM561KRTP-E	320 mm	1050 mm	250 mm	14 kg

Harmonizirana norma EN14511:2007, EN12102

Metode obračuna - mjerne norme PrEN 14825: 2011 Sekcija 8 i 9

Kontakt partner za dobivanje više informacija

Uvoznik / distributer u EU:
Toshiba Carrier UK Ltd.
Porsham Close, Belliver Industrial Estate,
PLYMOUTH, Devon, PL6 7DB.
United Kingdom