

Split klima uređaj

Outdoor unit	Single inverter	RAV-GM561ATP-E
Indoor unit	Slim Duct	RAV-RM561SDT-E

Function		Design load			Seasonal efficiency			
Cooling	Y	Cooling	Pdesignc	5.0 kW	Cooling	SEER	5.14	A
Grijanje - u prosjeku	Y	Heating/Average	Pdesignh	2.8 kW	Heating/Average	SCOP(A)	4.16	A+
Grijanje - toplije	N	Upravljanje kapacitetom = Varijabilno						
Grijanje - hladnije	N							

Cooling

Capacity				Učinkovitost			
Declared capacity for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.				Declared Energy efficiency ratio for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.			
Tj=35°C	Pdc	5.00 kW		Tj=35°C	EERd		2.62
Tj=30°C	Pdc	3.68 kW		Tj=30°C	EERd		4.10
Tj=25°C	Pdc	2.37 kW		Tj=25°C	EERd		7.24
Tj=20°C	Pdc	1.66 kW		Tj=20°C	EERd		9.45

Grijanje (prosječna klimatska zona)

Capacity				Učinkovitost			
Declared capacity for Heating/Average season, at indoor temperature 20°C and outdoor temperature Tj.				Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj.			
Tj=-7°C	Pdh	2.48 kW		Tj=-7°C	COPd		2.72
Tj=2°C	Pdh	1.51 kW		Tj=2°C	COPd		4.38
Tj=7°C	Pdh	0.97 kW		Tj=7°C	COPd		5.08
Tj=12°C	Pdh	0.95 kW		Tj=12°C	COPd		5.47
Tj=bivalent temperature	Pdh	2.48 kW		Tj=bivalent temperature	COPd		2.72
Tj=granična radna temperatura	Pdh	3.29 kW		Tj=granična radna temperatura	COPd		2.12
Bivalentna temperatura		-7 °C					
Granične radne temperature		-15 °C					

Electricity

Electric power input in power modes other than "on mode"

Sezonska snaga električnog priključka

Stanje isključenosti	Poff	0.012	kW	Cooling	QCE	340	kWh/a
Stanje mirovanja	Psb	0.012	kW	Heating/Average	QHE/A	943	kWh/a
Stanje isključenosti termostata	Pto	0.058	kW	Heating/Warmer	QHE/B	x	kWh/a
Način rada s grijačem kućišta	Pck	0.000	kW	Heating/Colder	QHE/C	x	kWh/a

Radni medij

Tip	R32		
Težina	0.90 kg		
Potencijal globalnog zatopljenja	GWP	675 kgCO ₂ eq.	

Sound power level - db(A)

Rated air flow - m³/h

	Cooling	Heating		Cooling	Heating
RAV-GM561ATP-E	63	65	RAV-GM561ATP-E	2400	2400
RAV-RM561SDT-E	60	60	RAV-RM561SDT-E	780	780

Dimenzije

	Visina	Širina	Dubina	Težina
RAV-GM561ATP-E	550 mm	780 mm	290 mm	40 kg
RAV-RM561SDT-E	210 mm	845 mm	645 mm	22 kg

Harmonizirana norma EN14511:2007 , EN12102

Metode obračuna - mjerne norme PrEN 14825: 2011 Sekcija 8 i 9

Kontakt partner za dobivanje više informacija
 Uvoznik / distributer u EU:
 Toshiba Carrier UK Ltd.
 Porsham Close, Belliver Industrial Estate,
 PLYMOUTH, Devon, PL6 7DB.
 United Kingdom