

## Split klima uređaj

Outdoor unit	Single inverter	RAV-GM561ATP-E
Indoor unit	4-way Cassette	RAV-RM561UTP-E

### Function

### Design load

### Seasonal efficiency

Cooling	Y	Cooling	Pdesignc	5.0 kW	Cooling	SEER	6.34	A++
Grijanje - u prosjeku	Y	Heating/Average	Pdesignh	2.8 kW	Heating/Average	SCOP(A)	4.60	A++
Grijanje - toplije	N	Upravljanje kapacitetom = Varijabilno						
Grijanje - hladnije	N							

## Cooling

### Capacity

Declared capacity for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.

### Učinkovitost

Declared Energy efficiency ratio for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.

Tj=35°C	Pdc	5.00 kW	Tj=35°C	EERd	3.21
Tj=30°C	Pdc	3.68 kW	Tj=30°C	EERd	4.75
Tj=25°C	Pdc	2.37 kW	Tj=25°C	EERd	8.61
Tj=20°C	Pdc	1.58 kW	Tj=20°C	EERd	14.36

## Grijanje (prosječna klimatska zona)

### Capacity

Declared capacity for Heating/Average season, at indoor temperature 20°C and outdoor temperature Tj.

### Učinkovitost

Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj.

Tj=-7°C	Pdh	2.48 kW	Tj=-7°C	COPd	2.84
Tj=2°C	Pdh	1.51 kW	Tj=2°C	COPd	4.69
Tj=7°C	Pdh	0.97 kW	Tj=7°C	COPd	5.92
Tj=12°C	Pdh	0.95 kW	Tj=12°C	COPd	6.95
Tj=bivalent temperature	Pdh	2.48 kW	Tj=bivalent temperature	COPd	2.84
Tj=granična radna temperatura	Pdh	3.29 kW	Tj=granična radna temperatura	COPd	2.17
Bivalentna temperatura		-7 °C			
Granične radne temperature		-15 °C			

## Electricity

Electric power input in power modes other than "on mode"

Sezonska snaga električnog priključka

Stanje isključenosti	Poff	0.012	kW	Cooling	QCE	276	kWh/a
Stanje mirovanja	Psb	0.012	kW	Heating/Average	QHE/A	852	kWh/a
Stanje isključenosti termostata	Pto	0.033	kW	Heating/Warmer	QHE/B	x	kWh/a
Način rada s grijačem kućišta	Pck	0.000	kW	Heating/Colder	QHE/C	x	kWh/a

## Radni medij

Tip				R32			
Težina				0.90	kg		
Potencijal globalnog zatopljenja	GWP				675	kgCO <sub>2</sub> eq.	

## Sound power level - db(A)

## Rated air flow - m<sup>3</sup>/h

	Cooling	Heating		Cooling	Heating
RAV-GM561ATP-E	63	65	RAV-GM561ATP-E	2400	2400
RAV-RM561UTP-E	47	47	RAV-RM561UTP-E	1050	1050

## Dimenzije

	Visina	Širina	Dubina	Težina
RAV-GM561ATP-E	550 mm	780 mm	290 mm	40 kg
RAV-RM561UTP-E	256 mm	840 mm	840 mm	20 kg

Harmonizirana norma EN14511:2007 , EN12102

Metode obračuna - mjerne norme PrEN 14825: 2011 Sekcija 8 i 9

Kontakt partner za dobivanje više informacija

Uvoznik / distributer u EU:  
Toshiba Carrier UK Ltd.  
Porsham Close, Belliver Industrial Estate,  
PLYMOUTH, Devon, PL6 7DB.  
United Kingdom