

## Split klima uređaj

Outdoor unit	Single inverter	RAV-GM801ATP-E
Indoor unit	Ceiling	RAV-RM801CTP-E

### Function

### Design load

### Seasonal efficiency

Cooling	Y	Cooling	Pdesignc	6.9 kW	Cooling	SEER	5.62	A+
Grijanje - u prosjeku	Y	Heating/Average	Pdesignh	5.1 kW	Heating/Average	SCOP(A)	4.21	A+
Grijanje - toplije	N	Upravljanje kapacitetom = Varijabilno						
Grijanje - hladnije	N							

## Cooling

### Capacity

Declared capacity for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.

### Učinkovitost

Declared Energy efficiency ratio for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.

Tj=35°C	Pdc	6.90 kW	Tj=35°C	EERd	2.90
Tj=30°C	Pdc	5.08 kW	Tj=30°C	EERd	4.27
Tj=25°C	Pdc	3.27 kW	Tj=25°C	EERd	6.20
Tj=20°C	Pdc	1.44 kW	Tj=20°C	EERd	13.93

## Grijanje (prosječna klimatska zona)

### Capacity

Declared capacity for Heating/Average season, at indoor temperature 20°C and outdoor temperature Tj.

### Učinkovitost

Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj.

Tj=-7°C	Pdh	4.51 kW	Tj=-7°C	COPd	2.25
Tj=2°C	Pdh	2.75 kW	Tj=2°C	COPd	4.35
Tj=7°C	Pdh	1.77 kW	Tj=7°C	COPd	5.81
Tj=12°C	Pdh	1.11 kW	Tj=12°C	COPd	6.44
Tj=bivalent temperature	Pdh	4.51 kW	Tj=bivalent temperature	COPd	2.25
Tj=granična radna temperatura	Pdh	3.31 kW	Tj=granična radna temperatura	COPd	2.11
Bivalentna temperatura		-7 °C			
Granične radne temperature		-15 °C			

## Electricity

Electric power input in power modes other than "on mode"

Sezonska snaga električnog priključka

Stanje isključenosti	Poff	0.012	kW	Cooling	QCE	429	kWh/a
Stanje mirovanja	Psb	0.012	kW	Heating/Average	QHE/A	1697	kWh/a
Stanje isključenosti termostata	Pto	0.045	kW	Heating/Warmer	QHE/B	x	kWh/a
Način rada s grijačem kućišta	Pck	0.000	kW	Heating/Colder	QHE/C	x	kWh/a

## Radni medij

Tip	R32		
Težina	1.30 kg		
Potencijal globalnog zatopljenja	GWP	675 kgCO <sub>2</sub> eq.	

## Sound power level - db(A)

## Rated air flow - m<sup>3</sup>/h

	Cooling	Heating		Cooling	Heating
RAV-GM801ATP-E	65	69	RAV-GM801ATP-E	2700	2700
RAV-RM801CTP-E	56	56	RAV-RM801CTP-E	1410	1410

## Dimenzije

	Visina	Širina	Dubina	Težina
RAV-GM801ATP-E	550 mm	780 mm	290 mm	42 kg
RAV-RM801CTP-E	235 mm	1270 mm	690 mm	29 kg

Harmonizirana norma EN14511:2007 , EN12102

Metode obračuna - mjerne norme PrEN 14825: 2011 Sekcija 8 i 9

Kontakt partner za dobivanje više informacija

Uvoznik / distributer u EU:  
Toshiba Carrier UK Ltd.  
Porsham Close, Belliver Industrial Estate,  
PLYMOUTH, Devon, PL6 7DB.  
United Kingdom