

Split klima uređaj

Outdoor unit	Single inverter	RAV-GP801AT-E
Indoor unit	Ceiling	RAV-RM801CTP-E

Function		Design load			Seasonal efficiency			
Cooling	Y	Cooling	Pdesignc	7.1 kW	Cooling	SEER	7.95	A++
Grijanje - u prosjeku	Y	Heating/Average	Pdesignh	5.1 kW	Heating/Average	SCOP(A)	5.05	A++
Grijanje - toplije	N	Upravljanje kapacitetom = Varijabilno						
Grijanje - hladnije	N							

Cooling

Capacity				Učinkovitost			
Declared capacity for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.				Declared Energy efficiency ratio for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.			
Tj=35°C	Pdc	7.10 kW		Tj=35°C	EERd		4.44
Tj=30°C	Pdc	5.32 kW		Tj=30°C	EERd		5.91
Tj=25°C	Pdc	3.36 kW		Tj=25°C	EERd		10.50
Tj=20°C	Pdc	2.24 kW		Tj=20°C	EERd		16.00

Grijanje (prosječna klimatska zona)

Capacity				Učinkovitost			
Declared capacity for Heating/Average season, at indoor temperature 20°C and outdoor temperature Tj.				Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj.			
Tj=-7°C	Pdh	4.51 kW		Tj=-7°C	COPd		3.43
Tj=2°C	Pdh	2.74 kW		Tj=2°C	COPd		5.08
Tj=7°C	Pdh	1.75 kW		Tj=7°C	COPd		6.49
Tj=12°C	Pdh	1.83 kW		Tj=12°C	COPd		7.82
Tj=bivalent temperature	Pdh	4.51 kW		Tj=bivalent temperature	COPd		3.43
Tj=granična radna temperatura	Pdh	1.20 kW		Tj=granična radna temperatura	COPd		1.41
Bivalentna temperatura		-7 °C					
Granične radne temperature		-27 °C					

Electricity

Electric power input in power modes other than "on mode"

Sezonska snaga električnog priključka

Stanje isključenosti	Poff	0.007	kW	Cooling	QCE	312	kWh/a
Stanje mirovanja	Psb	0.007	kW	Heating/Average	QHE/A	1412	kWh/a
Stanje isključenosti termostata	Pto	0.074	kW	Heating/Warmer	QHE/B	x	kWh/a
Način rada s grijačem kućišta	Pck	0.000	kW	Heating/Colder	QHE/C	x	kWh/a

Radni medij

Tip	R32		
Težina	1.90 kg		
Potencijal globalnog zatopljenja	GWP	675 kgCO ₂ eq.	

Sound power level - db(A)

Rated air flow - m³/h

	Cooling	Heating		Cooling	Heating
RAV-GP801AT-E	63	65	RAV-GP801AT-E	3180	3180
RAV-RM801CTP-E	41	41	RAV-RM801CTP-E	1410	1410

Dimenzije

	Visina	Širina	Dubina	Težina
RAV-GP801AT-E	1050 mm	1010 mm	370 mm	74 kg
RAV-RM801CTP-E	235 mm	1270 mm	690 mm	29 kg

Harmonizirana norma EN14511:2007 , EN12102

Metode obračuna - mjerne norme PrEN 14825: 2011 Sekcija 8 i 9

Kontakt partner za dobivanje više informacija

Uvoznik / distributer u EU:
Toshiba Carrier UK Ltd.
Porsham Close, Belliver Industrial Estate,
PLYMOUTH, Devon, PL6 7DB.
United Kingdom