

## Split klima uređaj

Outdoor unit	Single inverter	RAV-GP801AT-E
Indoor unit	Hi-wall Bi Refrigerant - R32 R410A	RAV-RM801KRTP-E

Function		Design load			Seasonal efficiency			
Cooling	Y	Cooling	Pdesignc	7.1 kW	Cooling	SEER	7.34	A++
Grijanje - u prosjeku	Y	Heating/Average	Pdesignh	5.1 kW	Heating/Average	SCOP(A)	4.13	A+
Grijanje - toplije	N	Upravljanje kapacitetom = Varijabilno						
Grijanje - hladnije	N							

## Cooling

Capacity			Učinkovitost		
Declared capacity for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.			Declared Energy efficiency ratio for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.		
Tj=35°C	Pdc	7.10 kW	Tj=35°C	EERd	3.45
Tj=30°C	Pdc	5.24 kW	Tj=30°C	EERd	5.57
Tj=25°C	Pdc	3.34 kW	Tj=25°C	EERd	9.28
Tj=20°C	Pdc	2.15 kW	Tj=20°C	EERd	16.54

## Grijanje (prosječna klimatska zona)

Capacity			Učinkovitost		
Declared capacity for Heating/Average season, at indoor temperature 20°C and outdoor temperature Tj.			Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj.		
Tj=-7°C	Pdh	4.51 kW	Tj=-7°C	COPd	2.78
Tj=2°C	Pdh	2.69 kW	Tj=2°C	COPd	4.08
Tj=7°C	Pdh	1.75 kW	Tj=7°C	COPd	5.30
Tj=12°C	Pdh	1.48 kW	Tj=12°C	COPd	6.73
Tj=bivalent temperature	Pdh	4.51 kW	Tj=bivalent temperature	COPd	2.78
Tj=granična radna temperatura	Pdh	0.93 kW	Tj=granična radna temperatura	COPd	0.88
Bivalentna temperatura		-7 °C			
Granične radne temperature		-27 °C			

## Electricity

Electric power input in power modes other than "on mode"

Sezonska snaga električnog priključka

Stanje isključenosti	Poff	0.009	kW	Cooling	QCE	338	kWh/a
Stanje mirovanja	Psb	0.009	kW	Heating/Average	QHE/A	1725	kWh/a
Stanje isključenosti termostata	Pto	0.050	kW	Heating/Warmer	QHE/B	x	kWh/a
Način rada s grijačem kućišta	Pck	0.000	kW	Heating/Colder	QHE/C	x	kWh/a

## Radni medij

Tip	R32		
Težina	1.90	kg	
Potencijal globalnog zatopljenja	GWP	675	kgCO <sub>2</sub> eq.

## Sound power level - db(A)

## Rated air flow - m<sup>3</sup>/h

	Cooling	Heating		Cooling	Heating
RAV-GP801AT-E	63	65	RAV-GP801AT-E	3180	3180
RAV-RM801KRTP-E			RAV-RM801KRTP-E		

## Dimenzije

	Visina	Širina	Dubina	Težina
RAV-GP801AT-E	1050 mm	1010 mm	370 mm	74 kg
RAV-RM801KRTP-E	mm	mm	mm	kg

Harmonizirana norma EN14511:2007, EN12102

Metode obračuna - mjerne norme PrEN 14825: 2011 Sekcija 8 i 9

Kontakt partner za dobivanje više informacija

Uvoznik / distributer u EU:  
Toshiba Carrier UK Ltd.  
Porsham Close, Belliver Industrial Estate,  
PLYMOUTH, Devon, PL6 7DB.  
United Kingdom