

Split klima uređaj

| | | |
|--------------|-----------------|----------------|
| Outdoor unit | Single inverter | RAV-GM801ATP-E |
| Indoor unit | 4-way Cassette | RAV-RM801UTP-E |

| Function | | Design load | | | Seasonal efficiency | | | |
|-----------------------|---|---------------------------------------|----------|--------|---------------------|---------|------|----|
| Cooling | Y | Cooling | Pdesignc | 6.7 kW | Cooling | SEER | 5.81 | A+ |
| Grijanje - u prosjeku | Y | Heating/Average | Pdesignh | 5.1 kW | Heating/Average | SCOP(A) | 4.42 | A+ |
| Grijanje - toplije | N | Upravljanje kapacitetom = Varijabilno | | | | | | |
| Grijanje - hladnije | N | | | | | | | |

Cooling

| Capacity | | | | Učinkovitost | | | |
|--|-----|---------|--|---|------|--|-------|
| Declared capacity for cooling at indoor temperature 27(19)°C and outdoor temperature Tj. | | | | Declared Energy efficiency ratio for cooling at indoor temperature 27(19)°C and outdoor temperature Tj. | | | |
| Tj=35°C | Pdc | 6.70 kW | | Tj=35°C | EERd | | 3.02 |
| Tj=30°C | Pdc | 4.94 kW | | Tj=30°C | EERd | | 4.49 |
| Tj=25°C | Pdc | 3.17 kW | | Tj=25°C | EERd | | 6.34 |
| Tj=20°C | Pdc | 1.41 kW | | Tj=20°C | EERd | | 14.16 |

Grijanje (prosječna klimatska zona)

| Capacity | | | | Učinkovitost | | | |
|--|-----|---------|--|--|------|--|------|
| Declared capacity for Heating/Average season, at indoor temperature 20°C and outdoor temperature Tj. | | | | Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj. | | | |
| Tj=-7°C | Pdh | 4.51 kW | | Tj=-7°C | COPd | | 2.30 |
| Tj=2°C | Pdh | 2.75 kW | | Tj=2°C | COPd | | 4.58 |
| Tj=7°C | Pdh | 1.77 kW | | Tj=7°C | COPd | | 6.12 |
| Tj=12°C | Pdh | 1.13 kW | | Tj=12°C | COPd | | 7.15 |
| Tj=bivalent temperature | Pdh | 4.51 kW | | Tj=bivalent temperature | COPd | | 2.30 |
| Tj=granična radna temperatura | Pdh | 3.31 kW | | Tj=granična radna temperatura | COPd | | 2.07 |
| Bivalentna temperatura | | -7 °C | | | | | |
| Granične radne temperature | | -15 °C | | | | | |

Electricity

Electric power input in power modes other than "on mode"

Sezonska snaga električnog priključka

| | | | | | | | |
|---------------------------------|------|-------|----|-----------------|-------|------|-------|
| Stanje isključenosti | Poff | 0.012 | kW | Cooling | QCE | 403 | kWh/a |
| Stanje mirovanja | Psb | 0.012 | kW | Heating/Average | QHE/A | 1615 | kWh/a |
| Stanje isključenosti termostata | Pto | 0.035 | kW | Heating/Warmer | QHE/B | x | kWh/a |
| Način rada s grijačem kućišta | Pck | 0.000 | kW | Heating/Colder | QHE/C | x | kWh/a |

Radni medij

| | | | |
|----------------------------------|---------|---------------------------|--|
| Tip | R32 | | |
| Težina | 1.30 kg | | |
| Potencijal globalnog zatopljenja | GWP | 675 kgCO ₂ eq. | |

Sound power level - db(A)

Rated air flow - m³/h

| | Cooling | Heating | | Cooling | Heating |
|----------------|---------|---------|----------------|---------|---------|
| RAV-GM801ATP-E | 65 | 69 | RAV-GM801ATP-E | 2700 | 2700 |
| RAV-RM801UTP-E | 50 | 50 | RAV-RM801UTP-E | 1230 | 1230 |

Dimenzije

| | Visina | Širina | Dubina | Težina |
|----------------|--------|--------|--------|--------|
| RAV-GM801ATP-E | 550 mm | 780 mm | 290 mm | 42 kg |
| RAV-RM801UTP-E | 256 mm | 840 mm | 840 mm | 20 kg |

Harmonizirana norma EN14511:2007 , EN12102

Metode obračuna - mjerne norme PrEN 14825: 2011 Sekcija 8 i 9

Kontakt partner za dobivanje više informacija
 Uvoznik / distributer u EU:
 Toshiba Carrier UK Ltd.
 Porsham Close, Belliver Industrial Estate,
 PLYMOUTH, Devon, PL6 7DB.
 United Kingdom